

Whidbey Millhouse® Easy-Fit T&G Paint Grade Shiplap	
Profile:	
Joint	Easy fit T&G / large tongue for hidden nailing
Gap	1/8 inch "nickel gap"
Thickness	1 1/16 inch
1x8	6-1/2" coverage (includes gap)
1x10	8-1/2" coverage (includes gap)
Wood Fiber:	
Structure	Solid wood / no MDF / no laminate / no glue
Species	Engelmann Spruce (<i>picea engelmannii</i>)
Origin	Rocky Mountains / High altitude
Mill certification	Sourced from SFI member mills
Manufactured	Made in USA / Freeland, Whidbey Island, Washington
Grain orientation	Mixed / Natural
Humidity	Kiln Dried 10-15%
Primer:	
Type	Sherwin Williams
Color	Grey
Application	High pressure rollers front and back
Appearance	Wood texture will be visible
Lengths:	
Assortment	Random 3' to 16' (see shipping length restrictions)
Maximum	0-5% 3' to 4'
Trimming	Ends may be untrimmed
Specified lengths	Ask about availability
Quality Description:	Applies to visible area after installation
A - grade quality	90-100% of pcs fit this classification
Knots	Yes
Holes	No through holes or voids
Cracks	Short and encased
Rot	No
End check	Max 1"
Color variation	Minimal to none
B - grade quality	0-10% of pcs fit this classification
Trim loss	0-5% of a piece may be lost due to trimming defect.
Defect	Small hole, void, split or profile variation
Installation:	
Fastening	Finish nailer
Hidden Nailing	Yes
Glue	No
Acclimation	Recommended for all wood products
Exterior	Spruce not recommended for exterior use.
Shipping:	
Shipping cost	Send request specifying volume and zip code
Minimum order	200 sqft
Nationwide	Max. 8' residential / Max. 10' U-pick trucking warehouse
Northwest WA	Max. 16'
Pick up:	
Minimum order	50 sqft.
Handling cost	Free
Paint/Stain notes:	
Sanding	Light sanding recommended
Staining	No
Paint	Paints well