Whidbey Millhouse® Unfinished VG FIR Flooring	
Profile:	
	T&G flooring profile
	Full 3/4 inch
	3-1/4" face width
	5-1/4" face width
Back relieved	
Wood Fiber	
	Douglas Fir (<i>Pseudotsuga menziesii</i>)
Grain orientation	
Grain density	
	Kiln dried 10-12%
*	Oregon
	Sourced from SFI member mills
	Made in USA / Freeland, Whidbey Island, Washington
	Yes. No laminate.
Laminated	
Lengths:	110
	Random 2' to 16' (see shipping length restrictions)
	5% 2' to 3'
	Ends may be untrimmed
Specified lengths	
Specifica lengtils	
Quality Description:	Applies to visible area after install
	90-100% of pcs fit this classification
Knots	
Holes	
Cracks/splits	
Rot	
End check	
	Yes (natural occurring)
	Light to none
	0-10% of pcs fit this classification
	0-5% of a piece may be lost due to trimming defect.
	Small knot, hole, split or profile variation
Delect	
Instillation:	
	Nail down
	Not required
Floating	
0	Wood, no particle board or cement
	Recommended for all solid wood flooring
Shipping:	Sand request specifying volume and gin code
	Send request specifying volume and zip code
Minimum order	
	Max. 8' residential / Max. 10' U-pick trucking warehouse
Northwest WA	Max. 16
Pick up:	
Minimum order	15U SqII.