Whidbey Millhouse® Unfinished VG FIR Porch Flooring	
Profile:	
	T&G flooring profile
	Full 3/4 inch
	3-1/4" face width
Back relieved	
<u> </u>	2.00
Wood Fiber	
Species	Douglas Fir (<i>Pseudotsuga menziesii</i>)
Grain orientation	Vertical (VG)
Grain density	Fine and Coarse grain
Humidity	Kiln dried 10-12%
Origin	Oregon
Mill certification	Sourced from SFI member mills
Manufactured	Made in USA / Freeland, Whidbey Island, Washington
	Yes. No laminate.
Laminated	No
_	
Lengths:	77 (77 (1) 1 11)
	Yes (Upon availability)
Trimming	Ends may be untrimmed
Tolerance	-0/+ 12
Quality Description:	Applies to visible area after install
	100% usable for painted porch floor
Knots	
Holes	No
Cracks/splits	No
Rot	No
End check	No
Color variation	Yes (natural occurring)
	Light to none
Instillation:	
	Nail down
	Not required
Floating	
Acclimation	Recommended for all solid wood flooring
Chinning	
Shipping:	Sand request specifying valume and zip code
Minimum order	Send request specifying volume and zip code
	Max. 8' residential / Max. 10' U-pick trucking warehouse
Northwest WA	IVIdX. 10
Pick up:	50 caft
Minimum order	ગ્રામકારા કર્યા.